

Product information | TECHNICAL DATA SHEET

ANTI-RUST PRIMER

400 ml, 10.7 Oz, 304 g.

GENERAL DESCRIPTION

Anti rust primer formulated with acrylic resins and corrosion inhibitor pigments, makes it ideal for protecting any iron surface.

FEATURES

- Fast drying.
- Good elasticity.
- Easy of application and recoating.
- Good adherence.
- Does not contain lead.
- High covering power.
- Very high resistance to outdoor exposure.
- High anti-corrosion power.

APPLICATIONS

Suitable as primer in spray paint systems. Its anticorrosive power makes it ideal as a primer coat for protecting any iron surface.

- Automotive industry
- Industrial applications
- Metal structures
- DIY
- Maintenance

INSTRUCTIONS FOR USE

- Shake can vigorously for one minute after hearing mixer noise.
- Thoroughly clean, degrease, and dry the object to be painted. On rusty metallic surfaces, remove corrosion using a wire brush.
- Apply thin coats for best results, always thin layers is better than one thick, paintable after ten minutes with the same paint.
- Disconnect the electrical appliance before painting. Use it in well ventilated areas.
- Request safety data sheets.

PHYSICAL PROPERTIES

Brinder type:	Acrylic
Color:	Gray, Red
Dry to the touch (ASTM D-1640 ISO 1517):	10'
Total drying (ASTM D-1640 ISO 1517):	30'
Thickness of dry layer (ASTM D-823 ISO 2808):	15 µ/layer
Adherence (ASTM D-3359 ISO 2409):	B
Theoretical coverage (continuous painting):	2,5 m² for 400 ml 0,70 m² for 150 ml
Thinner:	Butyl Acetate
Product life:	(Well Stored) 5 Years
Recoating:	After 10'
Painted resistance to heat:	160°C
Application conditions:	Ambient temperature 8°C Surface temperature 5-50°C Humidity Max. 85% R.H.P

*Adherence tests were performed on steel.

260126



APPEARANCE

DONUT
Indicates the paint color.

LID
Protects the valve and the nozzle.



LABEL



Gris / Gray
EX014PR0115

Rojo / Red
EX014PR0131

CAP SYSTEM



Pocket Cap
Fino - Fine

PACKAGING

Nominal capacity 400 ml.
Heat resistance of packaging: <50°C
Propellant: DME

Box (6 units)
205 X 140 X 200 mm.

