

Product information | TECHNICAL DATA SHEET

CANVAS VARNISH. Maximum protection for finishing canvases.
400 ml, 9.5 Oz, 270 g.

GENERAL DESCRIPTION

Transparent varnish formulated with an acrylic-resin base and UV protection that is easy to apply. Available in different finishes: gloss, matt and satin.

FEATURES

- Good hardening.
- Non-yellowing.
- Resistance to UV light.
- Good durability.
- Easy to apply and repaint.
- Good leveling.
- Good elasticity.

APPLICATIONS

Varnish for finishing coats on canvases painted with acrylic and oil paints. May also be applied to other types of materials to give them a protective coat.

INSTRUCTIONS FOR USE

- Shake the aerosol well before using, approximately for one minute after hearing the sound of the mixer. (For satin and matt finishes).
- Apply to clean and dry surfaces. Apply to totally dry colors in thin coats at a distance of 15-20 cm. To obtain a good quality finish, it is always best to apply three thin coats than one thick coat.
- On old and/or deteriorated artworks, do a prior cleaning and restoration of the surface and then proceed with the varnish coat. Oil paints should be dry before varnishing. Some oil paints can take months (even a year), depending on the thickness of the coat applied, until they are totally dry. We recommend doing a test on a small area and/or following the manufacturer's instructions.
- To clean nozzles, place the clogged nozzle on the solvent valve and press down to try to unclog.
- Never apply to equipment that is plugged in and use in well ventilated areas.
- Request safety datasheets.

PHYSICAL PROPERTIES

Binder:	Acrylic
Color:	Transparent
Shine 60°:	>80% shining 30-50% Satin 10% Mat
Dry touch (ASTM D-1640 ISO 1517):	1h
Completely dry (ASTM D-1640 ISO 1517):	12 h
Theoretical yeled (continuous painting):	2m ²
Solvent:	Mineral spirits or turpentine
Product life:	(Well Stored) 5 years
Application conditions:	T° Ambiente Mínima: 8°C
	T° Superficie: 5-50°C
	Humedad Máx 85% R.H.P

* The adhesion tests were conducted on PP (modified EPDM).

IMAGE



LABEL



CAP SYSTEM



Brillante / Glossy EX014PR1076	Satinado / Satin EX014PR1077	Mate / Matt EX014PR1078
-----------------------------------	---------------------------------	----------------------------

PACKAGING

Nominal capacity: 400 ml.
Heat resistance of packaging: <50°C
Propellant: DME

Box (6 units)
205 X 140 X 200 mm.

