

## Product information | TECHNICAL DATA SHEET

**GESSO PRIMER.** Prepares and primes surfaces to be painted.  
400 ml, 13 Oz, 370 g.

### GENERAL DESCRIPTION

Product developed for preparing, sealing, priming and improving color adhesion to most surfaces

### FEATURES

- Fast drying.
- Excellent flexibility.
- Easy to apply and repaint.
- Excellent adherence.
- Does not contain lead.
- High opacity.

### APPLICATIONS

Suitable for the preparation of canvas, wood, paper and metal. Do not use for the preparation of plastics or perform a test prior to use.

- Arts & crafts.
- Fine arts.
- DIY.

### INSTRUCTIONS FOR USE

- Shake well before use, one minute after hearing the sound of mixer.
- Apply over dry and cleaned surfaces. Remove corrosion. Over PP apply first a primer.
- Apply in thin coats to achieve better results, three thin coats are better than one thick coat.
- After use, turn can upside down and depress valve button for several seconds until only gas emerges so as to prevent clogging.
- Invertir el aerosol para purgar la válvula tras el uso, si se atasca el difusor reemplazarlo por uno de nuevo.
- Don't spray on plugged equipments and use it only in well ventilated areas.
- Ask for MSDS.

### PHYSICAL PROPERTIES

Binder	Polyurethane (PU) soluble in water
Color:	White
Dry to the touch (ASTM D-1640 ISO 1517):	30'
Completely dry (ASTM D-1640 ISO 1517):	24-48h'
Thickness of dry layer (ASTM D-823 ISO 2808):	20 µ/coat (2 coats)
Adherence (ASTM D-3359 ISO 2409):	B
Theoretical yield (pintado en continuo):	2,5 m <sup>2</sup>
Solvent:	Water / Alcohol
Product life:	(Well Stored) 5 years
Heat resistance of paint:	120°C
Condition for application:	Minimum T° 8°C
	Surface T° 5-50°C
	Max. humidity 85% R.H.P

\*The adhesion tests have been done on steel plate.

### IMAGE



### LABEL



Imprimación Gesso / Gesso Primer  
EX014PRO500

### CAP SYSTEM



### PACKAGING

Nominal capacity 400 ml.  
Heat resistance of packaging: <50°C  
Propellant: DME

Box (6 units)  
205 X 140 X 200 mm.

