

Product information | TECHNICAL DATA SHEET

WHITE AND GREY PRIMER

400 ml, 10 Oz, 295 g.

GENERAL DESCRIPTION

White primer paint formulated for use as a first layer or background, especially on dark surfaces, to ensure that the colors subsequently applied are brighter, especially when we want to finish the object with fluorescent paint or clear colors with a poor covering power.

Paint formulated for use as a primer, or even as a top coat when a matt white finish is required.

FEATURES

- Fast drying.
- Good adherence.
- Excellent covering power.
- Does not contain lead or other heavy metals.
- Color durability.
- Non-yellowing.
- Easy of application and recoating.

APPLICATIONS

Due to the nature of the product we recommend its use as a final top coat or as a primer for other paints.

- DIY
- Industrial applications
- Crafts
- Domestic

On certain plastics and polished metals apply a coat of primer.

INSTRUCTIONS FOR USE

- Shake can vigorously for one minute after hearing mixer noise.
- Apply thin coats for best results, always thin layers is better than one thick, paintable after ten minutes.
- Clean valve by holding can upside down and spraying until only clear gas comes out, if the diffuser gets clog, replace it for a new one.
- Disconnect the electrical appliance before painting. Use it in well ventilated areas.
- Request safety data sheets.

PHYSICAL PROPERTIES

Binder type:	Thermoplastic acrylic
Color:	White
Brightness 60° (ASTM D-523 ISO 2813):	<10%
Dry to the touch (ASTM D-1640 ISO 1517):	10'
Total drying (ASTM D-1640 ISO 1517):	20'
Thickness of dry layer (ASTM D-823 ISO 2808):	20 µm/layer (2 coats)
Theoretical yield (continuous painting):	2,5 m²
Product life:	(Well Stored) 5 years
Recoating:	After 10'
Heat resistance of paint:	160°C
Condition for application:	T° environment min 8°C
	T° surface min de 5°C-50°C
	Humidity max 85% R.H.P

*The adhesion tests were conducted on PP (EPDM modified).

260126

IMAGE



LABEL



CAP SYSTEM



Pocket Cap
Fino - Fine

Imprimación Blanco / White Primer
EX014PRO910

Imprimación Gris / Grey Primer
EX014PRO135

PACKAGING

Nominal capacity 400 ml.
Heat resistance of packaging: <50°C
Propellant: BP

Box (6 units)
205 X 140 X 200 mm.

